

# QEP 4 50Hz 1p

QEP Range




Genset image for illustration purposes only

Technical data		
Voltage	(V)	230
Frequency	(Hz)	50
Fuel		Diesel
Performance class		G1
Acoustic pressure LpA	(dB(A) @7m)	-
Acoustic power LwA	(dB(A))	-

Mechanical structure		
Length (L)	(mm)	760
Width (W)	(mm)	540
Height (H)	(mm)	560
Weight	(kg)	54
Fuel tank capacity	(l)	3.5
Wheels and handles		Optional

## Dimensions



Note: These drawings are provided for illustration purposes only.

## Engine

General		
Engine Brand		Yanmar
Engine Model		L70
R.P.M.		3000
Net Power	(kWm)	4.50
Fuel		Diesel
No. of cylinders		1
Displacement	(cm³)	320
Regulation type		Mechanic

Lubrication System		
Oil capacity	(l)	1.1
Engine Oil Guard		YES

Cooling System		
Cooling type		Air

Power ratings			
Prime	Prime	Standby	Standby
kW	kVA	kW	kVA
3.0	3.3	3.5	3.9
Power factor			0.9

## Fuel consumption table

Load level	PRIME	Aut. (h)
	(L/h)	
75%	0.93	3.76
100%	1.24	2.82

Starting system	
Recoil	YES
Electric 12V	NO

## Alternator

Alternator brand	NSM
Alternator model	K100E
IP alternator	IP23
Peak power 163°/27°	(kVA) 4,54
Poles	2
Excitation system	Capacitor Brushless
Efficiency at 100% 125°/40°	(%) 73

---

## Mains features and options

### Mains features

- Recoil start
- Fuel Cock
- Engine Oil Guard
- Sockets

### Sockets configuration

SCHUKO 230V 16A IP54	1
2P+T CEE 230V 16A IP44	1

### Options

- Wheel kit
- Differential circuit breaker, hourmeter (ELR)

## Regulations:

The generator set has a CE Marking that includes the following directives:

- 2006/42/CE Machine Safety.
- 2006/95/CEE Low Voltage.
- 2004/108/CE Electromagnetic compatibility.

### Definitions

#### Prime Rating

PRIME POWER: Electrical power data available at a variable load without limits of hours per year. An overload of 10% is allowed for 1 hour of every 12. In accordance with ISO 8528/1 (2005) – PRP

#### Standby

STANDBY POWER: Electrical power data at variable load in an emergency in accordance with standard ISO 8528/1 (2005) – ESP. Overloads of emergency power are not allowed.

Grupos Electr genos Europa, S.A. is a certified company with ISO 9001, ISO 14001, OHSAS 18001 and PECAL

Atlas Copco reserves the right to modify any characteristic of their equipment without prior warning.

All products are designed and engineered in Zaragoza Competence Center

Weight and dimensions of a standard generator set.

Non-contractual document

Grupos Electr genos Europa, S.A.

Central Offices:

Poligono pitarco II - Parcela 20

50450 Muel (Zaragoza) Espa a

Tel.: +34 976 145 432

Fax.: +34 976 145 431

DISTRIBUTED BY:



Please, contact your local Atlas Copco Dealer for more information